




สายคล้องประแจบ็อกฟรี

Stainless Wire Core With Direct Catch Hook For 1kg Load




- Direct catch slim hook can be connected to a tool directly.
- high flexibility, shape restoration and durability.

(mm)

Item No.	Color	Cord dia.	Core dia.	Normal Length	Max. Length	Unit Price
AR430DV	Violet	3.0	0.8	470	1700	770.-
AR430DR	Red					770.-
AR430DY	Yellow G					870.-
AR430DB	Clear Black					870.-
AR430DC	Clear					870.-

สายคล้องประแจบ็อกฟรี

Nylon Rope Core For 1kg Load




- Nylon rope core is used in a polyurethane
- Superior flexibility for smooth operation.

(mm)

Item No.	Color	Cord dia.	Core dia.	Normal Length	Max. Length	Unit Price
ARN10G	Green	5.5	3.0	520	1,700	520.-
ARN10Y	Yellow					480.-
ARN10P	Pink					480.-

สายคล้องประแจบ็อกฟรี

Kevlar Core For 1kg Load



**Fluorescent color


- Light weight with soft and extreme thin design.
- Kevlar core by DuPont Inc., USA is used in a polyurethane cord.

(mm)

Item No.	Color	Cord dia.	Core dia.	Normal Length	Max. Length	Unit Price
ARK10G	Green	2.5	1.2	490	1,820	400.-
ARK10R	Red					410.-
ARK10K	**Purple					500.-

สายคล้องประแจบ็อกฟรี

Stainless Wire Core For 500g Load



- Light weight with extreme thin cord, high flexibility and shape restoration

(mm)

Item No.	Color	Cord dia.	Core dia.	Normal Length	Max. Length	Unit Price
ARS05C	Clear	2	0.8	310	1,100	360.-
ARS05B	Black					360.-
ARS05R	Red					310.-

สายคล้องประแจบ็อกฟรี

Stainless Wire Core For 1kg Load

**Fluorescent color



- Stainless wire core is used in a Urethane cord.
- Superior flexibility and speedy coil shape restoration.

(mm)

Item No.	Color	Cord dia.	Core dia.	Normal Length	Max. Length	Unit Price
ARS10P	**Purple	3.0	1.0	480	2,300	490.-
ARS10R	**Red					530.-
ARS10Y	Yellow					500.-

สายคล้องเครื่องมือ


Stainless Wire Core For 2kg/3kg load



- Flexible and durable. Three-layer cord structure.

(mm)

Item No.	Color	Cord dia.	Core dia.	Normal Length	Max. Length	Unit Price
ARS20R	Red	4.0	1.2	410	1,600	330.-
ARS20W	White					380.-
ARS20B	Black					340.-
ARS30R	Red	5.0	1.2	410	1,400	540.-
ARS30W	White					560.-
ARS30B	Black					540.-

ลูกบ็อกพร้อมข้อต่อหัวปรับเอียงได้
Uni-Socket (for Impact Wrench)

USN 17~24

- Optimal for use in confined or deep spaces when assembling steel structured housing.



■ Example of use




(mm)

Item No.	Size (s)	d	Applicable bolts and nuts		Unit Price
			Standard	Small	
USN 17	17	25	M 10	M 12	460.-
USN 19	19	27	M 12	M 14	460.-
USN 24	24	34	M 16	M 18	460.-

ประแจปากตายข้างแฉก

Gear Wrench, Straight Type



(mm)

Item No.	Size	L	S	D	T1	T2	Unit Price
GRW8	8	140	16.0	17.0	4.5	6.5	330.-
GRW10	10	160	21.0	20.0	5.0	7.5	360.-
GRW12	12	171	24.5	23.0	5.5	8.5	390.-
GRW13	13	178	26.5	25.0	6.0	8.5	410.-
GRW14	14	191	28.5	27.0	6.5	9.0	430.-
GRW15	15	200	31.0	28.5	7.0	9.5	430.-
GRW17	17	225	34.5	31.5	7.5	10.5	500.-
GRW19	19	245	39.0	35.5	8.0	11.5	560.-
GRW21	21	290	45.0	40.5	9.0	13.0	880.-
GRW22	22	290	45.5	42.0	9.0	13.0	880.-
GRW24	24	335	51.5	47.0	10.0	14.5	950.-